

Package: cloudUtil (via r-universe)

October 12, 2026

Type Package

Title Cloud Utilization Plots

Version 0.1.12

Author Christian Panse <cp@fgcz.ethz.ch>, Ermir Qeli
<ermir.qeli@gmail.com>

Maintainer Christian Panse <cp@fgcz.ethz.ch>

Depends R (>= 2.11.0), methods

Description Provides means of plots for comparing utilization data of
compute systems.

License GPL-2

Collate cloudUtilPlot.R

URL <https://cran.r-project.org/package=cloudUtil>

NeedsCompilation no

Repository <https://cpanse.r-universe.dev>

Date/Publication 2016-06-09 15:19:22 UTC

RemoteUrl <https://github.com/cran/cloudUtil>

RemoteRef HEAD

RemoteSha 33a440a0d49b6f50b3c07bb0ca364287daa75ee2

Contents

cloudms2	2
cloudUtilPlot	2
Index	5

cloudms2	<i>Benchmark data set for cloudUtil</i>
----------	---

Description

The data set provides the measurements of benchmark using three compute infrastructures namely uzh.ch Schroedinger, Amazon EC2 (region us-east.), and the FGCZ internal compute server. The number crunching was done by doing tandem mass spectra peptide sequence assignments of a large scale proteomics Drosophila experiment similar to the data processing published here [E. Brunner, et. al., NBT, 2007] having approx. 1800 (LC)-MS/MS runs, 8474960 fragment ion spectra (tandem MS or MS2), identifying 498000 redundant and 72281 distinct peptides, and 9124 proteins. The data volume is approx. 0.3TB splitted into ~1800 jobs.

Format

A data frame with 10969 rows and 15 variables

References

<http://fgcz-transfer.uzh.ch/~cpanse/2011-10-24--pCloud.pdf>
<http://www.nature.com/nbt/journal/v25/n5/abs/nbt1300.html>

cloudUtilPlot	<i>Cloud Utilization Plot</i>
---------------	-------------------------------

Description

On the utilization graphic each horizontal line indicates the start and the end of one job. Color groups different runs.

Usage

```
cloudUtilPlot(group, begin, end, id,
               colormap,
               normalize,
               plotConcurrent,
               plotConcurrentMax,
               main)
```

Arguments

begin	a time series of the starting events; the time format is unix time stamp (seconds since Jan 01 1970).
end	a time series of the corresponding ending events.
id	identifiyer of each event.
group	group of each event.
main	an overall title for the plot.
colormap	color vector for the data. default is the rainbow colormap having as much colors as we have groups.
normalize	normalizes the time in a way that the groups are relative to each other; default is set to TRUE.
plotConcurrent	plot concurrent running tasks as solid lines; default is set to TRUE.
plotConcurrentMax	plot maximum of concurrent running tasks; default is set to FALSE.

Details

The cloudUtilPlot function requires the four arguments begin, end, group, and id. All other arguments are optional.

Author(s)

Christian Panse

References

Tyanko Aleksiev, Simon Barkow, Peter Kunszt, Sergio Maffioletti, Riccardo Murri, Christian Panse (2013), VM-MAD: a cloud/cluster software for service-oriented academic environments, <https://arxiv.org/abs/1302.2529>.

Examples

```
data(cloudms2)

#green
col.amazon<-rgb(0.1,0.8,0.1,alpha=0.2)
col.amazon2<-rgb(0.1,0.8,0.1,alpha=0.2)

#blue
col.fgc2<-rgb(0.1,0.1,0.8,alpha=0.2)
col.fgc22<-rgb(0.1,0.1,0.5,alpha=0.2)

#red
col.uzh<-rgb(0.8,0.1,0.1,alpha=0.2)
col.uzh2<-rgb(0.5,0.1,0.1,alpha=0.2)

cm<-c(col.amazon, col.amazon2, col.fgc2, col.fgc22, col.uzh, col.uzh2)
```

```
cloudUtilPlot(begin=cloudms2$BEGIN_PROCESS,  
              end=cloudms2$END_PROCESS,  
              id=cloudms2$id,  
              group=cloudms2$CLOUD,  
              colormap=cm,  
              normalize=FALSE,  
              plotConcurrent=TRUE);
```

```
cloudUtilPlot(begin=cloudms2$BEGIN_PROCESS,  
              end=cloudms2$END_PROCESS,  
              id=cloudms2$id,  
              group=cloudms2$CLOUD,  
              colormap=cm,  
              normalize=TRUE,  
              plotConcurrent=TRUE)
```

Index

* **datasets**

cloudms2, [2](#)

cloudms2, [2](#)

cloudUtil (cloudUtilPlot), [2](#)

cloudUtilPlot, [2](#)